

Pneumatic Piston End Tapped Vibrators *Models: 70-5/8, 70-3/4, 70-1, 70-1-1/4*

• Threaded inlet & outlet holes

- Air discharge thru exhaust manifold or vibrator
- Silent or impacting models
- Steel construction for long
 life



MODEL 70 END TAPPED PNEUMATIC PISTON VIBRATOR

VIBCO's Model 70 end-tapped piston series produce linear force that's fully adjustable with air pressure. The linear force and frequency will vary with air pressure. A self-starting spring is installed for fast starts in any piston position.

Model 70 pneumatic pistons are available in two styles: silent (air cushioned) or impacting (piston hitting end cap). Standard units exhaust through holes in the housing but can also be supplied with an exhaust manifold (EM) for attaching a muffler or hose to lead off exhaust air. Mounting hole can be inch or millimeter threaded for attaching to threaded rod or stud.

The patented Model 70 Pneumatic Piston Vibrator is entirely constructed of steel to assure a long life. These units are an inexpensive solution for moving material in small bins and hoppers as well as screens and small feeders.


Model 70 pneumatic pistons should be lubricated and operated with standard air cleaners. When ordering be sure to specify: inch or millimeter thread; S - for silent units and EM - if exhaust manifold is required.


800.633.0032 · www.VIBCO.com

DIMENSIONS

	Α		В		С		D		Е		F G		;	H*		I
Model	Inch	mm	Inch	mm	Inch	mm	Inch	mm	Inch	mm	Air Inlet	Inch	mm	Inch	mm	Air Exhaust
70-5/8	4-3/4	120	1-1/4	32	5/16-24	M8X1.25	1-5/16	33	5/8	16	1/8-NPT	2-3/8	60	2-3/8	60	1/4-NPT
70-3/4	4-3/4	120	1-5/8	41	3/8-24	M10X1.5	1-5/8	41	5/8	16	1/8-NPT	2-3/8	60	2-3/8	60	1/4-NPT
70-1	4-3/4	120	1-7/8	48	1/2-20	M12X1.75	1-7/8	48	5/8	16	1/8-NPT	2-3/8	60	2-3/8	60	1/4-NPT
70-1-1/4	8	203	2-5/16	59	1/2-20	M12X1.75	2-5/16	59	5/8	16	1/4-NPT	4	101	4	101	1/4-NPT

F






TECHNICAL DATA

Model 70	40 PSI/2.	.8 BAR	60 PSI/4.1 BAR		80 PSI/	5.5 BAR	WEI	GHT*	CONTENTS** IN BIN		
Piston								_			
Size	CFM	VPM	CFM	VPM	CFM	VPM	lbs.	kg.	lbs.	kg.	
5/8	2.5	9500	3	12000	4.5	14500	1	0.45	Up to 100	25	
3/4	3	9500	3.5	10500	5	13000	1.3	0.6	100-400	25-100	
3/4 S	2.5	7500	3	12000	4.5	14500	1.2	0.55	100-200	25-50	
1	5	7500	7	9000	8	11000	2.8	0.13	200-400	50-100	
1 S	3	6500	3.5	10500	5	13000	2.6	1.2	100-400	25-100	
1 1/4	5.5	6500	8	5500	10	7000	7	3.2	400-1000	100-250	
1 1/4 S	5	3750	7	9000	8	11000	6.8	3.1	300-800	75-200	

VIBCO AIR CANNONS:

HAVE A LARGER BIN OR HOPPER? STUBBORN OR COARSE MATERIAL?

CALL FOR A FREE AIR CANNON OR AIR BLASTER CATALOG TODAY.





Application Engineers, we will get you the vibrator that will work best for you. Try it for 10-days at NO RISK.

We're The Vibrator Guys."

VIBCO, INC. 75 Stilson Rd., P.O. Box 8

Wyoming, RI 02898 E-Mail: vibrators@VIBCO.com Phone: (401) 539-2392 FAX: (401) 539-2584

http://www.VIBCO.com

CANADA: 2215 Dunwin Drive Mississauga, Ont.L5L 1X1 Phone: (905) 828-4191 (800) 465-9709 FAX: (905) 828-5015

SOUTHEAST 12001 North Dr. Martin Luther King Dr. Unit 2703 Saint Petersburg, FL 33716 Phone: (401) 864-5117 FAX: (401) 578-9509

REV095-08

